

D2260-S INSTALLATION INSTRUCTIONS

A minimum of two people to erect and clamp the antenna to the mast is recommended.
Keep antenna and cables at a safe distance from any power lines.
To protect your antenna and receiver from lightning damage, ensure your equipment is grounded.

ANTENNA ASSEMBLY

1. Remove all 3 sections from the crate and place them on the ground.
2. Place the bottom of the 'Middle Section' in line with top of the 'Lower Section'.
3. Remove protective caps from the 'Lower Section', and 'Middle Section'.
4. Rotate 'Middle Section' as required so that slot of the 'Middle Section' is in line with the dowel pin located on the male coupling of the 'Lower Section'
5. Slide both sections together, attach and engage both clamps of the 'Lower Section' to the 'Middle Section'.
6. Repeat the above steps for installation of the 'Upper Section'.

MAST MOUNTING

1. Visually check to ensure all antenna clamps are attached and engaged.
2. Loosen the 2 clamping block screws as required, and slide the antenna onto the mast.
3. Ensure that the mast does not protrude above the clamp mount by more than 1/2".
4. Tighten the 2 clamping block screws.
5. Remove connector caps and attach down leads to the antenna.
6. Weatherproof all connections appropriate.

GROUNDING

1. Loosen the thumbscrew as required. Slide the grounding wire through the grounding hole, and tighten the thumb screw.
2. Connect the ground wire to the grounding device. If a grounding rod is used, the Grounding rod should be at least four feet in the ground.

