



CIVIL AVIATION YAGI ANTENNA

MODEL Y102B-130V

The Y102B-130V is a 118-137 MHz air traffic control 10 element Yagi antenna. The use of multiple driven elements allows our yagis to achieve high gain levels throughout their entire specified bandwidths. A single TACO Yagi's operational band typically covers a frequency range that would require as many as 3 standard Yagis. Each is furnished with an integrated 50 Ohm N-Female connector and includes a fiberglass mast fitted with coupling that center mounts to standard tower masts ranging from 1.66" to 2.875" OD.

ELECTRICAL				
FREQUENCY RANGE - MHz		118-137		
GAIN - dBi		11.2		
IMPEDANCE - Ohm		50		
POLARIZATION		Vertical		
VSWR - ° (Max)		2:1		
HPBW - °	Horz	60		
	Vertical	45		
STD CONNECTOR		N		
MAX INPUT POWER - W		280		
OPERATING TEMP - °C (°F)		-50 to 100 (-58 to 212)		

MECHANICAL			
NUMBER OF ELEMENTS	10		
OVERALL LENGTH - in (cm)	102.6 (260.6)		
ANTENNA WEIGHT – lbs (kg)	22 (10.0)		

ANTENNA PATTERNS			
AZIMUTH PATTERN	ELEVATION PATTERN		
330 346 360 365 0 € 10 16 30 36 35 35 35 35 35 35 35 35 35 35 35 35 35	10 0 0 156 150 150 150 150 150 150 150 150 150 150		

MOUNTING		
LENGTH & TYPE - in (cm)	52.6 (133.6) In Line Pipe Mount	
FIBERGLASS MAST OD - in (cm)	1.66 to 2.875 (42 to 73)	
AZIMUTH ADJUSTMENT - °	360	
` ,	,	

WIND LOADING			
WIND AREA - ft ²	No Ice	2.9	
WIND AREA - IL-	1⁄2" Radial Ice	5.25	
WIND LOAD - ft-lbs	*No Ice	90	
WIND LOAD - IC-IDS	**½" Radial Ice	52.5	

^{*} Wind Speed = 100 MPH at sea level with100% humidity at seventy degrees Fahrenheit

TACO Antenna's ongoing policy of continuing development may result in specification changes to its products.

TACO ANTENNA

(A division of Wade Antenna Inc.) 29 Sharp Road, Brantford, Ontario Canada N3T 5L8

www.tacoantenna.com

^{**} Wind Speed = 50 MPH at sea level with100% humidity at zero degrees Fahrenheit